



S88 / OPMI Vario from ZEISS

Magnification	Motorized ZEISS zoom, 1:6 ratio, adjustable via handgrip or foot control panel
Focusing system Varioskop®	Internal, motorized, continuously adjustable, triggered via handgrip or foot control panel
Working range	<ul style="list-style-type: none"> • 200 – 415 mm • 210 – 535 mm with Auxiliary Lens (optional)
Main binocular tube	<ul style="list-style-type: none"> • 0-180° Tiltable tube, f = 170 mm, 10x or 12,5x widefield eyepieces • Foldable tube f170 /f260, including PROMAG™ function for additional 50% magnification and integrated rotate function (optional)
Illumination	Superlux® 180 for main and backup illumination: 180 W xenon lamp with daylight color temperature, backup xenon lamp in fast-action changer
Rated voltage	(115 V): 100 V - 120 V (230 V): 220 V - 240 V
Rated frequency	50 Hz – 60 Hz
Power consumption	(115 V): max 1000 VA (230 V): max 2200 VA
Circuit breaker	Automatic
Weight:	<ul style="list-style-type: none"> • S88 floor stand with rigid column: Approx. 215 kg (with OPMI) • S88 floor stand with lifting column: Approx. 240 kg (with OPMI)

